Serial No.: 09/888,926

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A method of providing audio caller identification,

comprising the steps of:

receiving a call, the call being associated with a directory number;

querying a network database in a telecommunications network for caller identification

information, wherein the caller identification information comprises at least one of the directory

number associated with the call and a name associated with a calling party;

sending the caller identification information to a caller identification device; and

synthesizing and playing an audio message related to the caller identification information

associated with the call and simultaneously displaying the caller identification information

associated with the call on the caller identification device, wherein the audio message is stored

by the telecommunications network and wherein the caller identification information comprises

directory information.

2. (Currently Amended) The method of claim 1, further comprising the steps of:

prior to the step of synthesizing and playing an audio message, saving a recorded audio

message associated with the directory number;

comparing the directory number associated with the call with the directory number

associated with the recorded audio message;

if the directory number associated with the call matches the directory number associated

with the recorded audio message, playing the recorded audio message and simultaneously

displaying the caller identification information associated with the call; and

Serial No.: 09/888,926

- if the directory number associated with the call does not match the directory number associated with the recorded audio message, then performing the step of synthesizing and playing an audio message related to the caller identification information associated with the call, and <u>simultaneously</u> displaying the caller identification information associated with the call.

3. (Original) The method of claim 2, further comprising the steps of:

wherein the step of sending the caller identification information to a caller identification device includes ringing a telephone to which the caller identification device is functionally connected;

wherein the step of playing the recorded audio message and displaying the caller identification information associated with the call includes suspending ringing the telephone while playing the recorded audio message; and

wherein the step of playing an audio message related to the caller identification information associated with the call includes suspending ringing the telephone while playing the recorded audio message.

- 4. (Previously Presented) The method of Claim 1, wherein the audio message is played over a speaker functionally connected to the caller identification device.
- 5. (Currently Amended) A method of providing audio caller identification in an Advanced Intelligent Network, including a switch, a service control point, a service node and a database of caller identification information, wherein the service control point and the service node are functionally connected to the switch, and wherein the method comprises the steps of:

receiving a call from a calling party at a calling party switch directed to a called party at a called party switch;

sending call information associated with the call to the service control point, the call information including the directory number of the calling party;

Serial No.: 09/888,926

at the service control point, querying the database of caller identification information for

caller identification information associated with the call, wherein the caller identification

information comprises at least one of the directory number and a name associated with the

calling party;

causing the service node to synthesize and send an audio message related to the caller

identification information associated with the call to a called party caller identification device via

the called party switch; and

at the called party caller identification device, playing the audio message and

simultaneously displaying the caller identification information associated with the call, wherein

the caller identification information comprises directory information.

6. (Currently Amended) The method of claim:

The method of claim 5, further comprising the steps of:

prior to the step of synthesizing and sending an audio message, saving a recorded audio

message associated with a directory number;

at the service node, comparing the directory number associated with the call with the

directory number associated with the recorded audio message;

if the directory number associated with the call matches the directory number associated

with the recorded audio message, sending the recorded audio message to a called party caller

identification device via the called party switch;

at the called party caller identification device, playing the recorded audio message and

simultaneously displaying the caller identification information associated with the call; and

if the directory number associated with the call does not match the directory number

associated with the recorded audio message, then performing the step of causing the service node

to synthesize and send an audio message related to the caller identification information

associated with the call to a called party caller identification device via the called party switch.

Serial No.: 09/888,926

7. (Currently Amended) The method of claim 6, further comprising the steps of:

after the step of receiving a call from a calling party at a calling party switch directed to a called party at a called party switch, receiving at the service node a recorded audio message from the calling party directed to the called party;

sending the recorded audio message from the calling party to a called party caller identification device via the called party switch;

at the called party caller identification device, playing the recorded audio message from the calling party and displaying the caller identification information associated with the call; and

if no recorded audio message is received from the calling party directed to the called party, then performing the steps of;

if the directory number associated with the call matches the directory number associated with the recorded audio message, sending the recorded audio message to a called party caller identification device via the called party switch;

at the called party caller identification device, playing the recorded audio message and simultaneously displaying the caller identification information associated with the call; and

if the directory number associated with the call does not match the directory number associated with the recorded audio message, then performing the step of causing the service node to synthesize and send an audio message related to the caller identification information associated with the call to a called party caller identification device via the called party switch.

8. (Currently Amended) A system for providing audio caller identification, comprising:

a software module operative

Serial No.: 09/888,926

to query a network database in a telecommunications network for caller

identification information associated with a call from a calling party to a called party, the call

being associated with a directory number, wherein the caller identification information comprises

at least one of the directory number and a name associated with the calling party;

to send the caller identification information to a caller identification device;

the caller identification device, operative

to receive the caller identification information;

to synthesize and play an audio message related to the caller identification

information associated with the call and to simultaneously display the caller identification

information associated with the call on the caller identification device, wherein the caller

identification information comprises the directory number, wherein the caller identification

information comprises directory information, and wherein the audio message is stored by the

telecommunications network for playback by a speaker functionally connected to the caller

identification device.

9. (Currently Amended) The system of claim 8, wherein the caller identification

device is further operative

to save a recorded audio message associated with a directory number prior to

synthesizing and playing an audio message;

to compare the directory number associated with the call with the directory

number associated with the recorded audio message;

if the directory number associated with the call matches the directory number

associated with the recorded audio message, to play the recorded audio message and to

simultaneously display the caller identification information associated with the call; and

Serial No.: 09/888,926

if the directory number associated with the call does not match the directory

number associated with the recorded audio message, then to synthesize and play an audio

message related to the caller identification information associated with the call, and to display

the caller identification information associated with the call.

10. (Currently Amended) A method of providing audio caller identification,

comprising the steps of:

saving a recorded audio message associated with a directory number;

receiving a call, the call being associated with the directory number;

querying a database for caller identification information associated with the call, wherein

the caller identification information comprises at least one of the directory number and a name

associated with the calling party;

sending the caller identification information to a caller identification device, wherein the

caller identification information comprises directory information;

comparing the directory number associated with the call with the directory number

associated with the recorded audio message;

if the directory number associated with the call matches the directory number associated

with the recorded message, playing the recorded audio message and simultaneously displaying

the caller identification information associated with the call on the caller identification device;

and

if the directory number associated with the call does not match the directory number

associated with the recorded message, synthesizing and playing an audio message related to the

caller identification information associated with the call[[,]] and simultaneously displaying the

caller identification information associated with the call on the caller identification device.